Safety Data Sheet

Issue Date: 23-Nov-2015 **Revision Date:** 02-Mar-2026 **Version 2**

1. IDENTIFICATION

Product identifier

Product Name Angelus No. 507 Leather Dye

Other means of identification

SDS # ASP-004

UN/ID No UN1263

Recommended use of the chemical and restrictions on use

Recommended Use **Leather Shoe dye**

Details of the supplier of the safety data sheet

Supplier Address
Angelus Shoe Polish Co.
Florence Ave.
Santa Fe Springs, CA 90670
Ph: 562-941-4242

Emergency telephone number

Emergency Telephone INFOTRAC 1-352-323-3500 (International)
1-800-535-5053 (North America)

2. HAZARDS IDENTIFICATION

Appearance Transparent to deep color liquid **Physical state** Liquid **Odor** Slightly sweet, Alcohol

Classification

Flammable liquids	Category 2
Serious eye damage/eye irritation	Category 2

Label elements



Signal word
Danger

Hazard statements
Highly flammable liquid and vapor.
Causes serious eye irritation.

Precautionary Statements - Prevention
Wash face, hands and any exposed skin thoroughly after handling.
Wear protective gloves, protective clothing, eye protection and face protection.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
Keep container tightly closed.
Ground and bond container and receiving equipment.
Use only non-sparking tools.
Take action to prevent static discharges.
Use explosion-proof electrical, ventilating and lighting equipment.

Precautionary Statements - Response

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
If eye irritation persists: Get medical advice/attention.
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
In case of fire: Use CO_2, dry chemical, or foam for extinction.

Precautionary Statements - Storage
Store in a well-ventilated place. Keep cool.

Precautionary Statements - Disposal
Dispose of contents and container in accordance with local, regional, national, and international regulations as applicable.

Other Information
Toxic to aquatic life with long lasting effects.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	Weight-%
Ethyl Alcohol	64-17-5	30-60
1-Methoxy-2-propanol	107-98-2	10-30
o-Chlorotoluene	95-49-8	1-5
Ethylene Glycol Monobutyl Ether	111-76-2	1-5
Isopropyl Alcohol	67-63-0	1-5

If Chemical Name/CAS No is "proprietary" and/or Weight-% is listed as a range, the specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. FIRST AID MEASURES

Description of first aid measures

General Advice Provide this SDS to medical personnel for treatment.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation occurs.

Skin Contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.

Inhalation Remove exposed individual(s) to fresh air for 20 minutes. Consult a physician/poison center if individual's condition declines or if symptoms persist. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel.

Ingestion IF SWALLOWED: rinse mouth. Do not induce vomiting without medical advice. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. Immediately call a poison center or doctor/physician.

Most important symptoms and effects, both acute and delayed

Symptoms Contact with eyes may cause stinging, tearing, redness, or swelling. Contact with skin may result in redness and burning. If inhaled, symptoms may include, irritation of the nose, throat, and respiratory tract. Swallowing may result in gastrointestinal irritation (nausea, vomiting, and diarrhea), headache, dizziness, shortness of breath, drunken behavior, visual disturbance, fatigue, unconsciousness , complete blindness, and death.

Indication of any immediate medical attention and special treatment needed

Notes to Physician Gastric lavage may be effective by physician within 4 hours of ingestion.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media
Regular foam, water fog, CO2, dry chemical, Alcohol foam.

Unsuitable Extinguishing Media Not determined.

Specific Hazards Arising from the Chemical
Highly flammable liquid and vapor. Vapors may travel or be moved by air currents and ignited by pilot lights, other flames, smoking, sparks, static discharges or other ignition sources at locations distant from product handling point. Vapors may settle in low or confined areas or travel a long distance to an ignition source and flash back explosively. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution.

Hazardous combustion products Carbon monoxide. Carbon dioxide (CO2). Phosgene. Hydrogen chloride.

Explosion data
Sensitivity to Static Discharge Prevent electrostatic charge build-up by using common bonding and ground techniques.

Protective equipment and precautions for firefighters
As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Never use welding or cutting torch on or near containers that are full or empty because product (even slight residue) can ignite explosively. Cool fire exposed containers with water spray to prevent vapor pressure build up.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Wear protective clothing as described in Section 8 of this safety data sheet.

Environmental precautions

Environmental precautions Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information. See Section 12 for additional Ecological Information.

Methods and material for containment and cleaning up

Methods for Containment Persons not wearing protective equipment should leave area until cleanup is completed. Remove all sources of ignition. Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert (i.e. vermiculite, dry sand or earth) absorbent material.

Methods for Clean-Up Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. For waste disposal, see section 13 of the SDS.

7. HANDLING AND STORAGE

Precautions for safe handling

Advice on Safe Handling Wash face, hands and any exposed skin thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dust/fume/gas/mist/vapors/spray. Keep away from heat/sparks/open flames/hot surfaces. — No smoking. Ground/bond container and receiving equipment. Use explosion proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a dry, cool and well-ventilated place. Store locked up. Do not store above 49°C/120°F.

Packaging Materials Empty containers retain product residue and can be hazardous.

Incompatible Materials Strong oxidizing agents.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

Chemical name	ACGIH TLV	OSHA PEL	NIOSH
Ethyl Alcohol 64-17-5	STEL: 1000 ppm	TWA: 1000 ppm TWA: 1900 mg/m^3 (vacated) TWA: 1000 ppm (vacated) TWA: 1900 mg/m^3	TWA: 1000 ppm; TWA: 1900 mg/m^3; IDLH: 3300 ppm
1-Methoxy-2-propanol 107-98-2	TWA: 50 ppm STEL: 100 ppm	(vacated) TWA: 100 ppm (vacated) TWA: 360 mg/m^3 (vacated) STEL: 150 ppm (vacated) STEL: 540 mg/m^3	TWA: 100 ppm; TWA: 360 mg/m^3; STEL: 150 ppm STEL: 540 mg/m^3
o-Chlorotoluene 95-49-8	TWA: 50 ppm	(vacated) TWA: 50 ppm (vacated) TWA: 250 mg/m^3	TWA: 50 ppm; TWA: 250 mg/m^3; STEL: 75 ppm STEL: 375 mg/m^3
Ethylene Glycol Monobutyl Ether 111-76-2	TWA: 20 ppm	TWA: 50 ppm TWA: 240 mg/m^3 (vacated) TWA: 25 ppm (vacated) TWA: 120 mg/m^3 dSk Sdv	TWA: 5 ppm; TWA: 24 mg/m^3; IDLH: 700 ppm
Isopropyl Alcohol 67-63-0	TWA: 200 ppm STEL: 400 ppm	TWA: 400 ppm TWA: 980 mg/m^3 (vacated) TWA: 400 ppm (vacated) TWA: 980 mg/m^3 (vacated) STEL: 500 ppm (vacated) STEL: 1225 mg/m^3	TWA: 400 ppm; TWA: 980 mg/m^3; STEL: 500 ppm STEL: 1225 mg/m^3 IDLH: 2000 ppm

Appropriate engineering controls

Engineering Controls Apply technical measures to comply with the occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. Provide sufficient ventilation to maintain exposure below TLV(s). Any use of this product at an elevated temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.

Individual protection measures, such as personal protective equipment

Eye/Face Protection	Splash proof chemical safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.
Skin and Body Protection	Impervious gloves, clothes and boots. Refer to 29 CFR 1910.138 for appropriate skin and body protection.
Respiratory Protection	If TLV is exceeded, use a NIOSH/MSHA approved respirator for organic vapors; Refer to 29 CFR 1910.134 for respiratory protection requirements.
General Hygiene Considerations	Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Physical state	Liquid		
Appearance	Transparent to deep color liquid	**Odor**	Slightly sweet, Alcohol
Color	Clear	**Odor Threshold**	Not determined

Property	**Values**	**Remarks • Method**
pH	No data available	
Melting point / freezing point	No data available	
Initial boiling point and boiling range	No data	
Flash point	17.77 °C / 64 °F	
Evaporation rate	3	N-butyl acetate
Flammability (Solid, Gas)	Not determined	
Flammability Limit in Air		
Upper flammability or explosive limits	No data available	
Lower flammability or explosive limits	No data available	
Vapor Pressure	No data	
Relative vapor density	No data	
Relative Density	Not determined	
Water Solubility	Not determined	
Solubility in other solvents	Not determined	
Partition Coefficient	Not determined	
Autoignition temperature	No data available	
Decomposition temperature	Not determined	
Kinematic viscosity	Not applicable	
Dynamic viscosity	Not determined	
Particle characteristics	No data available	No data available
Explosive Properties	Not determined	
Oxidizing Properties	Not determined	

Other information

VOC Content	741 g/L
Liquid Density	7.5 lbs/gal @ 25°C(77°F)

10. STABILITY AND REACTIVITY

Reactivity
Not reactive under normal conditions.

Chemical stability
Stable under recommended storage conditions.

Possibility of hazardous reactions
None under normal processing.

Hazardous Polymerization Hazardous polymerization does not occur.

Conditions to Avoid
Keep away from heat, sparks and open flame.

Incompatible materials
Strong oxidizing agents.

Hazardous decomposition products
Carbon monoxide, Carbon dioxide (CO2), Various hydrocarbons, Hydrogen chloride, Phosgene.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information

Eye Contact Causes serious eye irritation.

Skin Contact Causes mild skin irritation.

Inhalation May be harmful if inhaled.

Ingestion May be harmful if swallowed.

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Ethyl Alcohol 64-17-5	= 7060 mg/kg (Rat)	-	= 116.9 mg/L (Rat) 4 h = 133.8 mg/L (Rat) 4 h
1-Methoxy-2-propanol 107-98-2	= 5000 mg/kg (Rat)	= 13 g/kg (Rabbit)	> 7559 ppm (Rat) 6 h
o-Chlorotoluene 95-49-8	= 3227 mg/kg (Rat)	> 2165 mg/kg (Rabbit)	= 7119 ppm (Rat) 4 h
Ethylene Glycol Monobutyl Ether 111-76-2	= 470 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	= 450 ppm (Rat) 4 h = 486 ppm (Rat) 4 h
Isopropyl Alcohol 67-63-0	4710 - 5840 mg/kg (Rat)	= 4059 mg/kg (Rabbit)	> 10000 ppm (Rat) 6 h

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms Please see section 4 of this SDS for symptoms.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Carcinogenicity Ethanol has been shown to be carcinogenic in long-term studies only when consumed as an alcoholic beverage. Isopropyl Alcohol (IPA) is an IARC Monograph Group 3 chemical. IPA is a Group 1 when manufactured by the strong-acid process.

Chemical name	ACGIH	IARC	NTP	OSHA
Ethyl Alcohol 64-17-5	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 1 - Carcinogenic to humans	Known Human Carcinogen	Present
1-Methoxy-2-propanol 107-98-2	A4 - Not Classifiable as a Human Carcinogen			
Ethylene Glycol Monobutyl Ether 111-76-2	A3 - Confirmed Animal Carcinogen with Unknown Relevance to Humans	Group 3 - Unclassifiable as to carcinogenicity in humans		
Isopropyl Alcohol 67-63-0	A4 - Not Classifiable as a Human Carcinogen	Group 3		Present

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)
A3 - Animal Carcinogen
IARC (International Agency for Research on Cancer)
Group 1 - Carcinogenic to humans
Group 3 - Not classifiable as to its carcinogenicity to humans
NTP (National Toxicology Program)
Known - Known Carcinogen
Occupational Safety and Health Administration of the US Department of Labor
X - Present

12. ECOLOGICAL INFORMATION

Ecotoxicity
Toxic to aquatic life with long lasting effects.

Component Information

Chemical name	Algae/aquatic plants	Fish	Crustacea
Ethyl Alcohol 64-17-5		LC50: 12.0 - 16.0mL/L (96h, Oncorhynchus mykiss) LC50: >100mg/L (96h, Pimephales promelas) LC50: 13400 - 15100mg/L (96h, Pimephales promelas)	LC50: 9268 - 14221mg/L (48h, Daphnia magna) EC50: =2mg/L (48h, Daphnia magna)
1-Methoxy-2-propanol 107-98-2		LC50: =20.8g/L (96h, Pimephales promelas)	EC50: =23300mg/L (48h, Daphnia magna)
o-Chlorotoluene 95-49-8		LC50: 70 - 100mg/L (96h, Brachydanio rerio)	
Ethylene Glycol Monobutyl Ether 111-76-2		LC50: =1490mg/L (96h, Lepomis macrochirus) LC50: =2950mg/L (96h, Lepomis macrochirus)	EC50: >1000mg/L (48h, Daphnia magna)
Isopropyl Alcohol 67-63-0	EC50: >1000mg/L (96h, Desmodesmus subspicatus) EC50: >1000mg/L (72h, Desmodesmus subspicatus)	LC50: =9640mg/L (96h, Pimephales promelas) LC50: =11130mg/L (96h, Pimephales promelas) LC50: >1400000µg/L (96h, Lepomis macrochirus)	EC50: =13299mg/L (48h, Daphnia magna)

Persistence/Degradability
Not determined.

Bioaccumulation
There is no data for this product.

Mobility

Chemical name	Partition coefficient
Ethyl Alcohol 64-17-5	-0.35
1-Methoxy-2-propanol 107-98-2	1
o-Chlorotoluene 95-49-8	3.42
Ethylene Glycol Monobutyl Ether 111-76-2	0.81
Isopropyl Alcohol 67-63-0	0.05

Other adverse effects
Not determined

13. DISPOSAL CONSIDERATIONS

Disposal methods

Disposal of Wastes Disposal should be in accordance with applicable regional, national and local laws and regulations.

Contaminated Packaging Disposal should be in accordance with applicable regional, national and local laws and regulations.

California Hazardous Waste Status This product contains one or more substances that are listed with the State of California as a hazardous waste

Chemical name	California Hazardous Waste Status
Ethyl Alcohol 64-17-5	Toxic Ignitable
Isopropyl Alcohol 67-63-0	Toxic Ignitable

14. TRANSPORT INFORMATION

Note Please see current shipping paper for most up to date shipping information, including exemptions and special circumstances.

DOT Consumer Commodity / Limited Quantity
- **UN/ID No** UN1263
- **Proper Shipping Name** Paint related material
- **Transport hazard class(es)** 3
- **Packing Group** II

IATA ID8000 / Consumer Commodity / Limited Quantity / Class 9 Packing Inst Y963
- **UN number or ID number** UN1263
- **Proper Shipping Name** Paint related material
- **Transport hazard class(es)** 3
- **Packing group** II

IMDG Consumer Commodity / Limited Quantity
- **UN number or ID number** UN1263
- **Proper Shipping Name** Paint related material
- **Transport hazard class(es)** 3
- **Packing Group** II

Marine Pollutant This material may meet the definition of a marine pollutant

15. REGULATORY INFORMATION

International Inventories

Chemical name	TSCA	TSCA Inventory Status	DSL/NDSL	EINECS/ELINCS	ENCS	IECSC	KECL	PICCS	AIIC
Ethyl Alcohol	X	ACTIVE	X	X	X	X	X	X	X
1-Methoxy-2-propanol	X	ACTIVE	X	X	X	X	X	X	X
o-Chlorotoluene	X	ACTIVE	X	X	X	X	X	X	X
Ethylene Glycol Monobutyl Ether	X	ACTIVE	X	X	X	X	X	X	X
Isopropyl Alcohol	X	ACTIVE	X	X	X	X	X	X	X

Legend:

TSCA *- United States Toxic Substances Control Act Section 8(b) Inventory*

DSL/NDSL *- Canadian Domestic Substances List/Non-Domestic Substances List*

EINECS/ELINCS *- European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances*

ENCS *- Japan Existing and New Chemical Substances*

IECSC *- China Inventory of Existing Chemical Substances*

KECL *- Korean Existing Chemicals Inventory*

PICCS *- Philippines Inventory of Chemicals and Chemical Substances*

AICS *- Australian Inventory of Chemical Substances*

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical name	CAS No.	Weight-%	SARA 313 - Threshold Values %
Ethylene Glycol Monobutyl Ether - 111-76-2	111-76-2	<4	1.0
Isopropyl Alcohol - 67-63-0	67-63-0	<1	1.0

CWA (Clean Water Act)

This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

US State Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Ethyl Alcohol 64-17-5	X	X	X
1-Methoxy-2-propanol 107-98-2	X	X	X
o-Chlorotoluene 95-49-8	X	X	X
Ethylene Glycol Monobutyl Ether 111-76-2	X	X	X
Isopropyl Alcohol 67-63-0	X	X	X

16. OTHER INFORMATION

NFPA	**Health hazards** -	**Flammability** -	**Instability** -	**Special hazards** -
HMIS	**Health hazards** -	**Flammability** -	**Physical hazards** -	**Personal protection** -

Issue Date: 23-Nov-2015
Revision Date: 02-Mar-2026
Revision Note: Regulatory Update

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet