SAFETY DATA SHEET

Angelus Roll Call Edge Finish Black

Prepared to the OSHA Hazard Communication Standard, 29 CFR 1910.1200

Revision date: November 5, 2026
Version: 2
Product code: ASP-035

SECTION 1 IDENTIFICATION

Product identifier	Angelus Roll Call Edge Finish Black
Product code	ASP-035
Other means of identification	SDS # ASP-035
Recommended use	Gloss edge finish.
Restrictions on use	Use only as directed.
Supplier	Angelus Shoe Polish Co. 12060 Florence Ave. Santa Fe Springs, CA 90670
Telephone	562-941-4242
Emergency telephone	INFOTRAC 1-800-535-5053 (North America); 1-352-323-3500 (International) (24 hr)

SECTION 2 HAZARD(S) IDENTIFICATION

Classification of the substance or mixture

Flammable liquids — Category 2
Serious eye damage / irritation — Category 2A
STOT SE 3 – narcotic effects — Category 3

Label elements



GHS02 GHS07

Signal word: **DANGER**

Hazard statements

H225	Highly flammable liquid and vapor.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

Precautionary statements — Prevention

P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P233	Keep container tightly closed.
P240	Ground and bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting equipment.
P242	Use non-sparking tools.
P243	Take action to prevent static discharges.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray.
P264	Wash hands thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.

P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statements — Response

P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use CO2, dry chemical, or foam to extinguish.

Precautionary statements — Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statements — Disposal

P501	Dispose of contents/container to an approved waste disposal plant.

Hazards not otherwise classified None known. Carbon black in this product is bound in the liquid and is not present as respirable dust; it is therefore not classified as a carcinogen in this form (see Section 11).

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Mixture

Chemical name	CAS number	Concentration (% w/w)
Acetone	67-64-1	80 – 100
Carbon Black	1333-86-4	5 – 10
1-Methoxy-2-propanol	107-98-2	1 – 5

NIOSH IDLH: Acetone 2500 ppm; Carbon Black 1750 mg/m3. NIOSH REL: Carbon Black TWA 3.5 mg/m3 (0.1 mg/m3 in presence of polycyclic aromatic hydrocarbons); 1-Methoxy-2-propanol TWA 100 ppm, STEL 150 ppm.

SECTION 4 FIRST-AID MEASURES

Inhalation IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Administer oxygen if breathing is difficult. Get medical attention.

Skin contact IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. Get medical attention if irritation occurs.

Eye contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

Ingestion IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If drowsy or unconscious, do not give anything by mouth; place individual on the left side with head down. If conscious, give 2 glasses of water to dilute. Get medical attention.

Most important symptoms and effects	Causes serious eye irritation. May cause drowsiness or dizziness.
Immediate medical attention / special treatment	Provide this SDS to medical personnel for treatment. Notes to physician: Treat symptomatically.

SECTION 5 FIRE-FIGHTING MEASURES

Suitable extinguishing media	Regular foam, carbon dioxide, or dry chemical.
Unsuitable extinguishing media	Not determined.
Specific hazards arising from the chemical	Highly flammable liquid and vapor. Vapors are heavier than air and may travel along the ground to ignition sources and flash back. This material may produce a floating fire hazard. Flame may be invisible. Approach fire with caution. Hazardous combustion products: Carbon monoxide, carbon dioxide (CO2). Sensitivity to static discharge: Prevent electrostatic charge build-up by using common bonding and grounding techniques.
Protective equipment and precautions for firefighters	As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Never use a welding or cutting torch on or near containers that are full or empty because product (even slight residue) can ignite explosively.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment, emergency procedures	Wear protective clothing as described in Section 8 of this safety data sheet. Remove all sources of ignition. Ventilate area of leak or spill.
Environmental precautions	Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.
Methods and materials for containment and cleanup	Prevent further leakage or spillage if safe to do so. Soak up and contain spill with an inert absorbent material (e.g. vermiculite, dry sand or earth). Use non-sparking hand tools and explosion-proof electrical equipment. Sweep up and shovel into suitable containers for disposal. For waste disposal, see Section 13.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling	Wash face, hands and any exposed skin thoroughly after handling. Avoid breathing dust/fume/gas/mist/vapors/spray. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Keep away from heat/sparks/open flames/hot surfaces. No smoking. Ground/bond container and receiving equipment. Use explosion-proof equipment. Use only non-sparking tools. Take precautionary measures against static discharges. Wear protective gloves/protective clothing and eye/face protection.
Conditions for safe storage, including incompatibilities	Keep container tightly closed and store in a cool, dry and well-ventilated place. Store locked up. Do not store above 49 °C/120 °F. Empty containers retain product residue and can be hazardous. Incompatible materials: Strong oxidizing agents. Strong acids. Strong alkalis.

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Component	OSHA PEL	ACGIH TLV
Acetone (67-64-1)	TWA 1000 ppm (2400 mg/m3)	TWA 250 ppm; STEL 500 ppm
Carbon Black (1333-86-4)	TWA 3.5 mg/m3	TWA 3 mg/m3 (inhalable particulate matter)
1-Methoxy-2-propanol (107-98-2)	Not established (vacated TWA 100 ppm; STEL 150 ppm)	TWA 50 ppm; STEL 100 ppm

Engineering controls Apply technical measures to comply with the occupational exposure limits. Ensure that eyewash stations and safety showers are close to the workstation location. Any use of this product in an elevated-temperature process should be thoroughly evaluated to establish and maintain safe operating conditions.

Eye / face protection Splash-proof chemical safety goggles. Refer to 29 CFR 1910.133 for eye and face protection regulations.

Skin / hand protection Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact. Refer to 29 CFR 1910.138 for appropriate skin and body protection.

Respiratory protection If TLV is exceeded, use a NIOSH/MSHA approved respirator. Refer to 29 CFR 1910.134 for respiratory protection requirements.

General hygiene Handle in accordance with good industrial hygiene and safety practice.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Physical state Liquid

Color Black/dark brown

Odor Mild acetone

Odor threshold Not determined

Melting / freezing point Not determined

Initial boiling point / range 56.1 °C / 133 °F

Flammability Highly flammable liquid and vapor

Lower / upper flammability or explosive limits Not determined

Flash point -15.5 °C / 4 °F, closed cup (TCC)

Auto-ignition temperature Not determined

Decomposition temperature Not determined

pH Not determined

Kinematic viscosity Not determined

Solubility Water solubility: not determined. Solubility in other solvents: not determined.

Partition coefficient: n-octanol/water Not determined (see Section 12 for component values)

Vapor pressure 185 mmHg @ 20 °C (68 °F)

Density / relative density Relative density 0.80; 6.7 lb/gal @ 25 °C (77 °F)

Relative vapor density Not determined

Particle characteristics	Not applicable (liquid)
VOC content	100 g/L

SECTION 10 STABILITY AND REACTIVITY

Reactivity	Not reactive under normal conditions.
Chemical stability	Stable under recommended storage conditions.
Possibility of hazardous reactions	None under normal processing. Hazardous polymerization does not occur.
Conditions to avoid	Keep away from heat, sparks and open flame.
Incompatible materials	Strong oxidizing agents. Strong acids. Strong alkalis.
Hazardous decomposition products	Carbon monoxide, carbon dioxide (CO2), various hydrocarbons.

SECTION 11 TOXICOLOGICAL INFORMATION

Likely routes of exposure	Eye contact: Causes serious eye irritation. Skin contact: May cause temporary irritation on skin contact. Inhalation: May cause drowsiness or dizziness. Ingestion: May cause gastrointestinal irritation, nausea, diarrhea, and vomiting.
Symptoms	See Section 4 of this SDS for symptoms.
Acute toxicity (numerical measures)	Mixture (calculated per GHS Chapter 3.1): ATEmix (oral) 5,834.00 mg/kg; ATEmix (dermal) 10,638.00 mg/kg; ATEmix (inhalation, vapor) 94.90 mg/L. Acetone (67-64-1): LD50 oral 5,800 mg/kg (rat); LD50 dermal >15,700 mg/kg (rabbit); LC50 inhalation 50,100 mg/m3 (rat, 8 h). Carbon Black (1333-86-4): LD50 oral >15,400 mg/kg (rat); LD50 dermal >3 g/kg (rabbit). 1-Methoxy-2-propanol (107-98-2): LD50 oral 5,000 mg/kg (rat); LD50 dermal 13 g/kg (rabbit); LC50 inhalation >7,559 ppm (rat, 6 h).
Delayed, immediate, and chronic effects	STOT - single exposure: May cause drowsiness or dizziness.
Carcinogenicity	Carbon Black (1333-86-4): ACGIH A3 (animal carcinogen); IARC Group 2B (possibly carcinogenic to humans). These listings apply to carbon black as a respirable dust. In this product, carbon black is bound in the liquid and is not present in respirable form, so the product is not classified as a carcinogen. No other component present at ≥0.1% is listed as a carcinogen by IARC, NTP, or OSHA.

SECTION 12 ECOLOGICAL INFORMATION (NON-MANDATORY)

Ecotoxicity	An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Acetone: fish LC50 6,210–8,120 mg/L (96 h, Pimephales promelas, static), 8,300 mg/L (96 h, Lepomis macrochirus), 4.74–6.33 mL/L (96 h, Oncorhynchus mykiss); crustacea EC50 10,294–17,704 mg/L and 12,600–12,700 mg/L (48 h, Daphnia magna, static). Carbon Black: crustacea EC50 5,600 mg/L (24 h, Daphnia magna). 1-Methoxy-2-propanol: fish LC50 20.8 g/L (96 h, Pimephales promelas, static), 4,600–10,000 mg/L (96 h, Leuciscus idus, static); crustacea EC50 23,300 mg/L (48 h, Daphnia magna).
Persistence and degradability	Not determined.
Bioaccumulative potential	Not determined.
Mobility in soil	Partition coefficient (log Kow): Acetone -0.24; 1-Methoxy-2-propanol -0.437.
Other adverse effects	Not determined.

SECTION 13 DISPOSAL CONSIDERATIONS (NON-MANDATORY)

Disposal methods	Disposal of wastes and contaminated packaging should be in accordance with applicable regional, national and local laws and regulations. US EPA waste number: Acetone (67-64-1) - RCRA U002; included in waste stream F039. California hazardous waste status: Acetone - Ignitable.

SECTION 14 TRANSPORT INFORMATION (NON-MANDATORY)

DOT (ground)	
UN number	UN1263
Proper shipping name	Paint related material
Transport hazard class	3
Packing group	II
Notes	IATA and IMDG: UN1263, Paint related material, Class 3, PG II. Please see current shipping paper for the most up-to-date shipping information, including exemptions and special circumstances.

SECTION 15 REGULATORY INFORMATION (NON-MANDATORY)

U.S. federal

International inventories: All components listed on TSCA, DSL/NDSL, EINECS/ELINCS, ENCS, IECSC, KECL, PICCS and AICS.
CERCLA: This material, as supplied, contains a substance regulated as a hazardous substance under CERCLA (40 CFR 302): Acetone (67-64-1), RQ 5,000 lb (2,270 kg).
SARA 313: This product does not contain any chemicals subject to the reporting requirements of Section 313 of Title III of SARA and 40 CFR Part 372.
CWA: This product does not contain any substances regulated as pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

State regulations

State Right-to-Know (New Jersey, Massachusetts, Pennsylvania): Acetone, Carbon Black, 1-Methoxy-2-propanol.

California Proposition 65

This product does not contain chemicals known to the State of California to require a Proposition 65 warning.

SECTION 16 OTHER INFORMATION

Revision date

November 5, 2026

Version

2

Changes in this revision

Original issue 15-Aug-2014; previous revision 05-May-2022 (Version 1). This revision: converted to the current GHS format; product name limited to Black; Section 3 concentrations given as OSHA prescribed ranges; eye irritation specified as Category 2A; hazards not otherwise classified and restrictions on use added; carbon black stated as bound in the liquid and Proposition 65 listing removed; relative density corrected to 0.80; ATEmix inhalation corrected to vapor; OSHA carcinogen notation removed; supplier street address added.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.